

Simulating Receptor-Flexible
Small Molecule binding
Using AutoDock

S. Ravichandran, Ph.D.
Advanced Biomedical Computing Center (ABCC)
National Cancer Institute Frederick
Frederick, MD 21702

05/25/2004

Email: sravi@ncifcrf.gov

Tel: 301 846 1991

<http://nciiris.ncifcrf.gov/~ravichas/docking>

Goals of Docking

Fitting a small molecular (drug molecule) into a protein

Docking two proteins together

novel inhibitor discovery using molecular databases

Things U need

1) Structures of protein/small molecule

Molecule	Databases	Method
Protein/DNA	PDB	x-ray, NMR
Small Molecules	CSD	x-ray

2) Software:

Program to do docking: Dock, AutoDock
Ludi, FlexX
3D-Dock etc.

3) Powerful Computers: CPU, disk-space
etc.

Questions to ask before docking:



Critical analysis of the protein structures

What to do with bound ions, water molecules? Remove them? Why?

Crystal structure - Rigid nature - bound ions and water are held in the active site. Are they valid configurations?

Resolution of the structure?
High resolution/thermal factors

NMR: Which conformation/model to choose?



Loosely bound complex

The docking activity gives the proteins the ability to promote and inhibit (or accelerate or prevent) certain chemical reactions.


Importance:

Designing bioactive compounds,
Computer-Aided Drug design

.....

.....

..... and many more



HIV-Protease complex with tripeptide inhibitor

Things we know:

- a) HIV protease: enzyme in the AIDS virus, important for its replication
- b) Chemical reaction takes place in protease at an active site
- c) Inhibitor drugs bind to the active site and block the functioning


?s we ask:

- a) Binding affinity of the drug
- b) What has to be changed for better binding


Drug Design

Immunophilin FKBP soluble receptor
for the natural immunosuppressant
drug FK506

Aim: Find strong-binding ligands
that can substitute for the natural
FK506



9



Lin et al, JACS 2002, 124, 5632





Figure 4. Location of 2 and 9 in the docked complex. 9 was docked in the presence of 2.

AMBER was used to perform MD & snap-shot conformations were taken and docked using AutoDock

MD



Problem:

To find molecular binding sites
(hot-spots) by computer

Why is it difficult?


2 Rigid molecules

6 degrees of freedom
(3-rotational, 3 translational)

In addition if you assume the
small drug sized molecules to be
flexible (say 14 degrees of free
dom)

1028 variations

Even difficult with
a **SUPER COMPUTER!!!!**



Atom-based tools are usually slower than the matching methods & considered also better becos of the assumed flexibility of the ligands.

1990: Drs. **David S. Goodsell;**
Arthur J. Olson;
Garrett M. Morris;
Ruth Huey; Scott Halliday
RikBelew...

Scripps Research Institute
La Jolla, CA

Original Version: f77
Currently: C++
(ver 3.0.5)

AutoDockTools
(ADT)

Free for Academics

Michel Sanner & Ruth Huey
Scripps Research Institute

GUI to prepare and submit jobs
for AutoDock
Code written in Python


- Optimization
Global minimum or maximum
of a function with
following properties:

Continuous function
Domain Range

Search techniques:

Local: Operation which iteratively improves its estimate of minimum by searching for better solutions in a local neighbourhood of current solution

Global: Will perform a sophisticated search across several multiple local minimum



$$\text{Energy} = V_{\text{vdw}} + V_{\text{coul}} + V_{\text{hb}}$$

$$V_{\text{vdw}} = \sum_{i,j} 4\epsilon_{ij} \left[(A_{ij}/r_{ij})^{12} - (B_{ij}/r_{ij})^6 \right]$$

$$V_{\text{coul}} = \sum_{i,j} (q_i q_j) / [4\pi\epsilon(r)\epsilon_0 r_{ij}]$$

Pairwise
Additive



(Const dielectric or distance dependent)


H- bonding 12-10 form is used


Empirical relationship between molecular structure and binding free energy

$$\Delta G = K_{\text{vdw}} * V_{\text{vdw}} + K_{\text{hb}} * V_{\text{hb}} + K_{\text{ele}} * V_{\text{coul}} \\ + K_{\text{tor}} * V_{\text{tor}} + K_{\text{sol}} * V_{\text{sol}}$$


Coefficients are empirically determined using linear regression analysis from a set of Protein-ligand complexes with known binding constants.







Model Receptor
(NR = 10)



Model Ligand
(NL = 4)

Energy Calculation:

11	12	13	14	15	16	17	18	19	110
21	22	23	24	25	26	27	28	29	210
31	32	33	34	35	36	37	38	39	310
41	42	43	44	45	46	47	48	49	410

Total Terms = NL * NR

To deal at each simulation step

Example: Biotin has 19 atoms

**Receptors of the range of
1000 or more atoms**

(1000 x 19 = 19000) terms !!!!

**AutoDock we will be doing
million steps on GA**

**so, 19000 * Million Interactions
per Simulation**



**How to avoid this Computational
Heaviness without losing information?**

**AutoDock uses GRID(s) to precalculate
the energies due to all the atoms
of the ligands and store them.**



**These grids are like LOOKUP-TABLES
and used to lookup the interaction
energies later**

**The Grid Method makes the energy
calculations independent of the
size (number) of the Receptor!!**








That is all OK,
What is a GRID?

Imagine the ligand
has 4 atoms of 3 atom
types



1-D Rep.

Possible Maps for the model 17 Ligand



(or one can do
a PB calculation
to calculate ϕ)


Electron
MAP
If you want
to study
Electrostatics?

Automated Docking

Conflicting Requirements

- a) desire for a robust and physically relevant procedure
- b) Computation demands at a reasonable level

Static Receptor – Mobile small drug molecule
Grid-based model




Methods of docking:

- a) Simulated Annealing:
- b) Genetic Algorithms:

Annealing is a process in which temperature of the substance is reduced (slowly) until the material crystallizes in a single crystal (usually corresponds to global minimum free-energy)

Simulated Annealing: Computational method of mimicking annealing.

SA can be used to do both global and local search. Global at high Temperature and local at low temperatures.



S.Ravichandran, ABCC
NCI, sravi@ncifcrf.gov

Simulated Annealing

Monte Carlo

Cycle

$$T_i = (gT_{i-1})$$

Random changes to ligand position, orientation and/or conformation

Compute new E_1

Is E_1 is lower than E_0 ?

Yes

NO

Accept the changes

accepted with prob $e^{(-\Delta E/k_B T)}$


Is the number of acceptances or rejection are within the chosen number?

No

Yes

End Cycle

Receptor



Ligand

Does random walk around the receptor

Evolutionary Computing

I. Rachenberg 1960

Genetic Algorithm

(ideas taken from
Natural Genetics
& Biological Evolution)

Genetic Programming

Darwin, John Holland, 1975
John Koza, 1992.....

Living Organism

CELL

Same set of
Chromosomes
(strings of DNA)

Serves as a
model for
the whole
organism

Genetic Algorithms are usually
used to carry out Global Search.

Genes

Hybrid Genetic Algorithm

How big?

Set of solutions (Populations
or Chromosomes)

What are
chromosomes?

Generate population of
n chromosomes

What is
fitness?

Evaluate the fitness $f(x_i)$

Crossover how often?
Mutation how often?
Elitism? Selection?

Create new population
Elitism Selection
Crossover Mutation

No

Is Termination Condition
(Max # of Energy Eval.
or Generations) satisfied?


No Explicit
Termination conditions

Yes

STOP


Chromosome 1

E1



Chromosome 2

E2




Different
Position &
Orientation

and so on

If E1 is lower than E2
probably 1 will eventually
survive compared to 2

Classical GA represent genome as a fixedlength bit string

24



Transl. Gene

Rot. Gene

Torsion Gene

Generation

Mapping & fitness *translates genotypes–phenotypes to calculate E*

Fitness *Which individuals will reproduce based on worst energy individual*

Crossover *2–point crossover*

Parent 1



+

Parent 2



=

Offspring



Mutation *random changes to variables using Cauchy distribution*

Elitism *How many top individuals survive into next generation?*

Crossover

2-point crossover 25

Parent 1




+

Parent 2




=

Offspring



2 offsprings



Issues with GA:

- 1) Premature convergence
- 2) Too long for convergence
How many runs?
How many energy
evaluations?
- 3) Choice of parameters

Initialize population

Repeat

Evaluate Solutions in the population

Perform Competitive Search

Apply Genetic Operators

Perform Local Search

Until Convergence Criteria Satisfied

Pseudo Code for GA

Ph.D. Thesis of
W.E. Hart (1994)

AutoDock Tools (ADT)

Freeware

Dr. Micheal Sanner
Molecular Graphics Lab
Scripps Research Institute
La Jolla, CA

ADT provides GUI interface for setting up and using AutoDock

<http://www.scripps.edu/pub/olson-web/people/sanner>

1) Sybyl

Receptor:

PDB → Add essential H → Fix charges Kollman
United charges → save as Mol2 file

Ligand:

PDB → check for atom types → add all H →
fix charges → save as mol2 file

2) type *adt* at the system prompt

AutoTors

- 1) Read the ligand molecule
- 2) Use Autotors to setup the tree and branches
- 3) Toggle torsion activity
- 4) Aromatic Carbons C→ A
- 5) Non-Polar hydrogens (merge or restore)

AutoGpf (grid parameter file)

- 1) Read the macromolecule
- 2) If the solvation parameters are not added ADT queries whether to add them, if you say yes, it converts the mol2 file to pdbqs file
- 3) Set Map types
- 4) Set grid maps
- 5) Write GPF or edit GPF

AutoDpf (docking parameter file)

- 1) Read the macromolecule**
- 2) Read the ligand**
- 3) Select Docking algorithm**
- 4) Set docking run parameters**
- 5) write or edit DPF file**


Start

- 1) Start AutoGrid**
- 2) Start AutoDock**
- 3) Options to submit jobs in other SGIs**
- 4) Cancel the jobs**

Test Case

Streptavidin/Biotin (1stp) (2.6 Ang Resol)

Weber et al 1989



Autogrid:

Number of points:

116, 104, 124 (x,y,z),

$117 \times 104 \times 124 = 1508832$

Grid Spacing = 0.375 Ang.

Map types C,H,N,S,O & e

CPU Time: 7.53s AutoGrid

Octane SGI workstation

Docking: LGA-LS, Population Size = 50;

Elitism = 1, Cross-over rate = 0.8

rate of mutation = 0.02, GA_num_evals 250000


Lowest Docked Energy Mean	Mean Docked Energy	Number in Cluster	Ref. RMSD	Est Free Ene. of Binding
-10.78	-10.46	6	0.39	9.03

CPU Time: 3m 25.13s

Octane SGI workstation

Streptavidin/Biotin complex (1stp)

P.C. Weber, D.H. Ohlendorf, J.J. Mendolowski, and F.R. Salemme (1992)



Bound Conformation
Lowest Energy Conformation

Violet
Red



Things to know:

Not possible to find whether a ligand will bind with millimolar, micromolar or nano-molar binding constants

Genetic Algorithm methods are non-deterministic (successive runs may not produce the same answer). Also there is no guarantee that the solution identified by GA will be the best solution.

Useful Links

<http://w3.to/autodock>

<http://nciiris.ncifcrf.gov/~ravichas/docking>



HAPPY DOCK!